

Declaration of Performance

CE DoP 5/206699/12

The undersigned, representing the following:

Company placing on the market:
NSG Group, Haydnstraße 19, Gelsenkirchen 45884, Germany

Manufacturing Plant:
Watson Street Works, St Helens, United Kingdom

Product
Pilkington Texture **Reeded™**, Annealed, 4 mm

The performance of the product identified above is in conformity with the set of detailed performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.


Harmonised standard : EN 572-9: 2004

Intended use : Basic soda lime silicate glass, intended to be used in buildings and construction works

Declared Performance

Essential Characteristics	AVCP Systems	Performance
Resistance to Fire	1	NPD
Reaction to Fire	3,4	A1
External Fire Performance	3,4	NPD
Bullet Resistance	1	NPD
Explosion Resistance	1	NPD
Burglar Resistance	3	NPD
Pendulum Body Impact Resistance	3	NPD
Resistance Against Sudden Temperature Changes and Temperature Differentials	4	40 K
Wind, Snow, Permanent and Imposed Load Resistance	4	33 MPa
Direct Airborne Sound Insulation	3	29 (-2; -3) dB
Thermal Properties	3	5.8 W/m ² K
Radiation Properties		
Light Transmittance / Reflectance	3	0.88/0.08/0.08
Solar Transmittance / Reflectance	3	0.78/0.07/0.07

Notified Bodies 0336



Kristian Chalmers
Head of Sales
03/12/2021



Neil Syder
Head of UK Operations
03/12/2021